

D5TLP Dump Series

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • G.V.W.R.-9,950 # • G.A.W.R.(Each Axle) - 5,200 # • Coupler - 2 5/16" Adjustable • Safety Chain - 3/8 grade 43 with hooks • Jack -7,000 # drop leg • Frame - all tubing construction • Fenders - 10"x72" diamond plate with backs • Tongue - 6" channel wrap around • 12 volt self contained pump | <ul style="list-style-type: none"> • Axles - 2-5,200 # cambered brake axles • Suspension - Double eye spring with equalizer • Tires - 225-75-15" load range D • Wheel -15" 6 bolt white spoke • Deck - 12 ga. smooth steel • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel • Stake pockets on sides • Sides- 14 ga. Smooth steel |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Standard Features

Optional Features

| | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> • 15" white spoke wheels • Light protectors • Electric breakaway • E-Z Lube axles • 6Ft Ramp with Track • 4" Bore Hydraulic Cylinder • Charge post | <ul style="list-style-type: none"> • Higher sides • 2-Way side and top hinge gate • Double barn doors • Tarp System • Charger |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Dimensions

| Length | A | B | C | D | E |
|--------|------|-----|-------|-----|-----|
| 10' | 120" | 79" | 40.5" | 28" | 76" |
| 12' | 144" | 91" | 40.5" | 28" | 76" |

