



Gooseneck 7 Ton Series

<ul style="list-style-type: none"> • G.V.W.R. - 14,000 # • G.A.W.R.(Each Axle) - 7,000 # • Coupler - 2-5/16" adjustable • Safety Chain - 3/8 grade 43 with hooks • Jack -10,000 # drop leg • Frame-12 @ 16 # I-beam • Crossmembers - 3" channel on 16" center • Side rails - 6" channel with stake pockets on 24" center with rub rails • Locking toolbox in neck 	<ul style="list-style-type: none"> • Axles - 2 Dexter 7,000# single wheel electric brake axles • Suspension -Multi-leaf slipper spring with equalizer • Tires - 235-80R-16" load range D • Wheel - 6.75 x 16" 8 bolt white spoke • Deck - 2" pressure treated pine • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel
--	---

Standard Features Optional Features

<ul style="list-style-type: none"> • Crossmembers on 16" centers • Sealed modular wiring harness • Electric breakaway • E-Z Luble axles • 5' Dovetail • 5' Ramps • Spare tire mt. 	<ul style="list-style-type: none"> • Dual jacks • Steel deck • Deck over neck • Vacuum over hydraulic • Electric over hydraulic • Headache rack • Popup dovetail • 5th Wheel option
--	---

Dimensions

Length	A	B	C	D	E
25'	300"	178"	91"	37"	96"
29'	348"	226"	91"	37"	96"

