



Workhorse Series

• G.V.W.R. - 20,000 #	• Axles - 2 Dexter 10,000# dual wheel electric brake axles
• G.A.W.R.(Each Axle) - 10,000 #	• Suspension - Multi-leaf slipper spring with equalizer
• Coupler - 2-5/16" adjustable	• Tires - ST 235/ 80R16 Load Range "E"
• Safety Chain-3/8 grade 43 withhooks	• Wheel - 6.75 x 16" dual 8 bolt
• Jacks - Dual 10,000 # drop leg side crank	• Deck - 2" pressure treated pine
• Frame -w12 x 19 I-beam	• Lights - D.O.T. Stop, tail, turn, and clearance
• Crossmembers -3" Structural Channel	• Elec. Plug - 7-way RV
• Side rails - 6" channel with stake pockets on 24"center with rub rails	• Paint - High solids acrylic enamel

Standard Features

Optional Features

• 16" dual wheels	• Steel deck
• Crossmembers on 16" centers with Pierced frame	• Deck over neck
• Sealed modular wiring harness	• 12 Ton capacity
• Electric breakaway	• Vacuum over hydraulic
• Oil bath Axles	• Electric over hydraulic
• 5' Self cleaning Dovetail	• Headache rack
• Deck level Ramps	• D-Rings
• Rubber mt. lights	• Pop-up Dovetail
• Spare tire mt.	• Wood-covered ramps
• Keyed Security lock for storage box	• 5th Wheel
	• Double 2-speed jacks

Dimensions

Length	A	B	C	D	E
25'	300"	192"	91"	37"	96"
29'	348"	207"	91"	37"	96"
31'	372"	224"	91"	37"	96"
33'	396"	240"	91"	37"	96"
35'	420"	272"	91"	37"	96"

