

GEQ6T Series

<ul style="list-style-type: none"> • G.V.W.R.-12,000 # • G.A.W.R.(Each Axle) - 6,000 # • Coupler - 2 - 5/16" adjustable gooseneck • Safety Chain - 3/8 grade 43 with hooks • Jack -10,000 # drop leg • Frame -8" channel • Crossmembers - 3" channel • Fenders - 10"x72" diamond plate with backs • Tongue - 8" channel gooseneck • Bed width - 81" 	<ul style="list-style-type: none"> • Axles - 2-6,000 # cambered brake axles • Suspension - Slipper spring with equalizer • Tires - LT 750 - 16" load range E • Wheel -16" 8 bolt white spoke • Deck - 2" pressure treated pine • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug - 7-way RV • Paint - High solids acrylic enamel • Ramps - 4' fold down • Sealed modular wiring harness
---	--

Standard Features

Optional Features

<ul style="list-style-type: none"> • 16" white spoke • Pressure treated decking • Light protectors • Electric breakaway • E-Z Lube axles • Spare tire mt. 	<ul style="list-style-type: none"> • Side rails • Steel deck • 48" split gate • Dual jacks • D-Rings • Self Cleaning Dovetail
---	---

Dimensions

Length	A	B	C	D	E
16'	192"	136"	91"	28.25"	81"
18'	216"	148"	91"	28.25"	81"
20'	240"	160"	91"	28.25"	81"
22'	264"	172"	91"	28.25"	81"

