



LS Utility Series

<ul style="list-style-type: none"> • G.V.W.R. - 2,900 # • G.A.W.R. - 3,500 # • Coupler - 2" coupler • Safety Chain - 3/16 grade 30 with hooks • Jack - 2,000 # top wind • Frame - 3"x2"x 3/16" angle • Crossmembers - top 3"x2"x3/16 angle • Fenders - 9"x32" roll formed with back • Floor Height 20" 	<ul style="list-style-type: none"> • Axles - 3,500 # cambered E-Z lube • Suspension - Multi-leaf spring • Tires - 205-75-15" load range C • Wheel - 15" 5 bolt white spoke • Deck - 2". pressure treated pine • Lights - D.O.T. Stop, tail, turn, and clearance • Elec. Plug - 4-way flat • Paint - High solids acrylic enamel
---	--

Standard Features Optional Features

<ul style="list-style-type: none"> • 15" white spoke rims • Pressure treated decking • Light protectors • E-Z Lube Axles 	<ul style="list-style-type: none"> • 24" sides • Expanded metal sides • Swingup jacks • Double fold gate
--	--

Dimensions

Trailer size	A	B	C	D	E
5X8'	96"	55.5	38.5	20"	60"
5X10'	120"	69.5	38.5	20"	60"
5X12'	144"	86.5"	38.5	20"	60"
5x14'	168"	98.5"	38.5	20"	60"
6X10'	120"	69.5"	38.5	20"	76"
6X12'	144"	86.5"	38.5	20"	76"

